

< FWD

FWD SUPERSTRUCT BHD NOTCHED FOR ALUM SQ TUBE RAIL

FLEXIBLE DRAW LATCH OR OTHER HARDWARE TO SECURE HATCH IN OPEN POSITION (MCMaster-CARR 1685A66 OR TBD)

SQUARE SLEEVE BEARING CARRIAGES (X2) MCMaster-CARR 60255K53 8 FASTENERS (1/4"-20) FROM HATCH FRAME UNDERSIDE TO THREADED HOLES IN CARRIAGES

UPPER RAIL 1.5" X 1.5" X .250" WALL, RADIUS CORNERS 6061 ALUM SQ TUBE *RAIL & TRACK ORIENTED DIRECTLY FORE-AFT*

SLIDING HATCH BODY 1/2" BRONZE-TINTED ACRYLIC

SLIDING HATCH FRAME HDPE(?)

LOWER TRACK MACHINED HDPE *RAIL & TRACK ORIENTED DIRECTLY FORE-AFT* FWD EDGE OF TROUGH CAN ACT AS STOP FOR HATCH SLIDE

RAIL END SUPPORT MCMaster-CARR 60255K33 BOLTED TO SUPERSTRUCT BHD OR MCMaster-CARR 60255K35 WELDED TO SUPERSTRUCT BHD (IF BHD CUT-OUT LIMITS MOUNT HEIGHT) -ADD SET SCREW TO FIX RAIL

LATCH SOUTHCO MF-02-110-60 OR SIMILAR (CATCH IN AFT COAMING)

GRABRAIL 3/4" NOMINAL SCH40 ALUM OR SIMILAR

AFT COAMING HDPE OR OTHER

